

REMARKS

Version With Markings To Show Changes Made

Attached hereto is a marked-up version of the changes made to the claims by the current amendment. The attached pages are captioned VERSION WITH MARKINGS TO SHOW CHANGES MADE.


Summary

The foregoing amendments eliminate the multiple dependency of claims 3, 7 and 8 thereby reducing the filing fee. An early action on the merits of this application is respectfully requested.

Respectfully submitted,

Date: July 3, 2003

By:


Bruce H. Troxell
Reg. No. 26,592

TROXELL LAW OFFICE PLLC
5205 Leesburg Pike, Suite 1404
Falls Church, Virginia 22041
Telephone: (703) 575-2711
Telefax: (703) 575-2707

VERSION WITH MARKINGS TO SHOW CHANGES MADE

IN THE CLAIMS:

Claims 3, 7 and 8 have been amended and new claims 9, 10 and 11 have been added as follows:

3. (Amended) The adjustable support apparatus for monitor in the car as claim 1[or 2], wherein the front, middle and rear connecting means are conjugated by a hole, a screw bolt and a nut, and the front connecting means is coupled to the pivotal rod by a hole, a screw bolt and a nut.

7. (Amended) The adjustable support apparatus for monitor in the car as claim 1[or 6], wherein the front connecting members have a hole at the front opposite a hole of pivotal rod for conjugating by a screw bolt and a nut.

8. (Amended) The adjustable support apparatus for monitor in the car as claim 1[or 6], wherein the rear connecting members have a hole at the front opposite a hole of second means for conjugating by a screw bolt and a nut.

9. (New) The adjustable support apparatus for monitor in the car as claim 2, wherein the front, middle and rear connecting means are conjugated by a hole, a screw bolt and a nut, and the front connecting means is coupled to the pivotal rod by a hole, a screw bolt and a nut.

VERSION WITH MARKINGS TO SHOW CHANGES MADE

10. (New) The adjustable support apparatus for monitor in the car as claim 6, wherein the front connecting members have a hole at the front opposite a hole of pivotal rod for conjugating by a screw bolt and a nut.

11. (New) The adjustable support apparatus for monitor in the car as claim 6, wherein the rear connecting members have a hole at the front opposite a hole of second means for conjugating by a screw bolt and a nut.